## characteristics ESD Basic 2 with castors

Article: 9151E fabric

Dimensions in mm	Backrest:	H:	430
	Seat:	H:	470-610
		B:	460
		T:	440
Packing data	Weight	kg	14,5
	Volume	m³	0,18



		Benefit
Conductivity	The metal components have a conductive coating The high-comfort upholstery is also conductive Typical discharge resistance of 10^6 Ohm Conductive glides.	Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1. 100% ESD protection.
Backrest	Large, ergonomically designed backrest to take the strain off the spine and muscles with integrated lumbar support.	Healthy posture due to a hump providing support for the back in the lumbar region.
	Backrest height adjustment convenient and easy to handle in sitting position.	The support area can be adapted in accordance to the user's body size.
Seat	Ergonomically designed seat with rounded front edge.	The round front edge of the seat prevents blocked circulation in the thighs.
Finishes for seat and backrest	ESD fabric upholstery: Resistant, breathable and comfortable ESD-fabric Duotec Selectable in following colours: Black (9801) Blue (9802) Grey (9811) Red (9803)	This high-quality fabric upholstery is breathable and can both absorb and expel moisture. The extremely soft surface guarantees maximum comfort.
Seat height	Stepless seat height setting from 470 - 610 mm supported by safety gas spring with protective cover.	Seat height can be adapted to nearly 95 % of all body sizes, the cover protects the gas spring from dust and dirt
Functions / Mechanism	Permanent contact backrest	This mechanism ensures that the backrest responds immediately to any movements of the upper body by following them. Thus, the back remains supported all the time. The backrest can also be locked into any tilt position if required.
	Quick adjustment	Every function can be operated comfortable and easy in sitting position.
Base	Anti-Shock lock  Black 5 star base made from steel shape tube, conductive, powder-coatet, black.	The backrest cannot accidentally spring forwards even after the lock has been released.  Very high stability, longevity.  Flat design prevents stumbling hazard.
	Flat design.	riat design prevents stumbling hazard.
Castors	Conductive Dual-wheel safety castors with load-sensitive brakes, for hard floors as standard.	Chairs are braked when not used which decreases the accident risk.
Materials	The materials used are recyclable.	Environmentally friendly.

## characteristics ESD Basic 2 with castors

Article: 9151E fabric

Warranty

Dimensions in mm	Backrest:	H:	430
	Seat:	H:	470-610
		B:	460
		T:	440
Packing data	Weight	kg	14,5
	Volume	m³	0,18



100% ESD protection.

Procuring is insured.

Standards DIN EN European standard 61340-5-1 for

ESD-protected areas
DIN 68 877 German GS "safety tested" mark

of confirmity

Quality Management System DIN EN ISO

9001

Regulation EWG Nr. 1836/93 and

Environmental.

10 year long term warranty, 3 years full

warranty.

Guaranteed quality and high efficiency.

## characteristics ESD Basic 2 with castors

Article: 9151E fabric

Backrest:	H:	430
Seat:	H:	470-610
	B:	460
	T:	440
Weight	kg	14,5
Volume	m³	0,18
	Seat:	Seat: H: B: T: Weight kg



Options		Benefit
Armrests	Loop armrests	Made of polyamide, adjustable in width (20 mm).
	Multifunctional armrest ESD	The armrests are adjustable in height, width and depth to suit the individual user. Further, they are conductive.
Accessories	Foot ring.	The foot ring can be retrofitted by attaching it to the chair column.
Options	ESD plus option	With volume conductive plastic parts and frame
	Light grey frame	
	Polished aluminium base	